

Temperieren.
Kühlen.
 Filtern.
 Entwickeln.
 Projektieren.

Kompressorkühler Serie RW ax (Axial-Lüfter, bürstenlos)

Modelle	Kühlleistungen		Leistungsaufnahme Gesamt ⁽¹⁾⁽²⁾		Leist.-Aufn. Kompressor ⁽¹⁾	An- schlüsse	Abmessungen	Gewicht
	[kW]	[kCal/h]	RWA/C [kW]	RWE [kW]				
RW-2ax	2,1	1.810	1,27	1,1	0,64	R ½	560x620x1230	210
RW 6 ax	6	5.160	2,39	2,21	1,68	R ¾	750x750x1200	250
RW 8 ax	8,7	7.480	2,82	2,64	2,1	R ¾	900x750x1200	260
RW 10 ax	11,6	9.980	3,42	3,24	2,53	R 1	1100x690x1300	270
RW 13 ax	14,2	12.210	3,56	3,38	2,67	R 1	1100x690x1300	280
RW 19 ax	19,6	16.860	5,67	5,29	3,94	R 1	1200x800x1350	300
RW 26 ax	26,7	22.960	7,13	6,6	5,25	R 1¼	1200x900x1350	340
RW 30 ax	32	27.520	8,07	7,54	6,2	R 1¼	1120x1060x1200	400
RW 39 ax	36,6	31.480	9,59	8,46	7,14	R 1½	1270x1200x1460	440
RW 51 ax	48,4	41.620	12,19	11,59	8,84	R 1½	1130x1130x1460	680
RW 51/2 ax	53,4	45.920	13,96	13,36	2 x 5,25	R 1½	1320x1130x1750	760
RW 60 ax	58	49.880	13,56	12,96	10,34	R 1½	1730x860x1780	740
RW 60 ax-2GR	64	55.040	15,75	15,15	2 x 6,2	R 1½	1150x1130x1800	700
RW 60/2 ax	64	55.040	15,84	15,24	2 x 6,2	R 1½	1680x1330x2160	800
RW 78 ax-2GR	73,2	62.950	18,58	17,48	2 x 7,14	R 2	1150x1330x2160	750
RW 78/2 ax	73,2	62.950	18,38	17,28	2 x 7,14	R 2	1680x1330x2160	900
RW 102/2 ax	97	83.420	23,58	22,48	2 x 8,84	R 2	1680x1320x2160	1050
RW 116 ax	97	83.420	26,56	25,06	2 x 8,84	R 2	1730x1150x2220	1150
RW 116 ax-2GR	116,2	99.930	26,56	25,06	2 x 10,34	R 2½	1730x1150x2160	1050
RW 116/2 ax	116,2	99.930	27,08	25,58	2 x 10,34	R 2½	2100x1130x1970	1300
RW 156/2 ax	146,4	125.900	37,68	35,18	4 x 7,14	R 2½	2260x1330x2360	1400
RW 204/2 ax	194	166.840	45,12	43,32	4 x 8,84	R 3	2145x1330x2260	1700
RW 232/2 ax-4GR	232	199.520	51,12	49,32	4 x 10,34	R 3	2300x1730x2160	1800
RW 232/2 ax	232	199.520	52,24	50,44	4 x 10,34	R 4	3680x1130x1920	1900
RW 312/4 ax	293	251.980	76,54	72,04	8 x 7,14	R 4	4280x1320x2260	2100
RW 408/4 ax	388	333.680	89,74	86,24	8 x 8,84	R 4	4480x1330x2260	2200
RW 464/4 ax	464	399.040	103,82	100,32	8 x 10,34	R 5	3580x1780x2200	2300
RW 624/4 ax	595	511.700	155,48	151,98	8 x 13,7	R 5	4520x2300x2260	3200

Die technischen Daten können Änderungen unterliegen.

(1) Kühlleistung: +15°C Wasser, +25°C Luft

(2) Zur Leistungsauslegung kontaktieren Sie uns bitte.